

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no : SDS 00589

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

Air Liquide UK Ltd.
Station Road Coleshill
B46 1JY Birmingham
United Kingdom
safety.aluk@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 01675 462695 (Available 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Gases under pressure : Compressed gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 4	H332
	Reproductive toxicity, Category 1A	H360D
	Specific target organ toxicity – Repeated exposure, Category 2	H373

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS04

GHS07

GHS08

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H280 - Contains gas under pressure; may explode if heated.
H332 - Harmful if inhaled.
H360D - May damage the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

4 Component mix in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Reference number: SDS 00589

Precautionary statements (CLP)

- Prevention : P280 - Wear protective gloves, protective clothing, eye protection.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe gas, vapours.
- Response : P308+P313 - IF exposed or concerned: Get medical advice/attention.
P304+P340+P315 - IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.
- Storage : P403 - Store in a well-ventilated place.
- Supplemental information : Restricted to professional users.

2.3. Other hazards

None.
Not classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: --- REACH-no: *1	75.1686	Press. Gas (Comp.), H280
Carbon dioxide	CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: --- REACH-no: *1	19.5	Press. Gas (Liq.), H280
Carbon monoxide	CAS-No.: 630-08-0 EC-No.: 211-128-3 EC Index-No.: 006-001-00-2 REACH-no: 01-2119480165-39	5	Flam. Gas 1B, H221 Press. Gas (Comp.), H280 Acute Tox. 3 (Inhalation:gas), H331 Repr. 1A, H360D STOT RE 1, H372
Nitric oxide	CAS-No.: 10102-43-9 EC-No.: 233-271-0 EC Index-No.: --- REACH-no: 01-2120766630-54	0.275	Ox. Gas 1, H270 Press. Gas (Comp.), H280 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 1 (Inhalation:gas), H330
Propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	0.0564	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Ensure adequate air ventilation.
Stay upwind.
See section 8 of the SDS for more information on personal protective equipment.
- For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.
Avoid release of product into atmosphere.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Only experienced and properly instructed persons should handle gases under pressure.
Consider pressure relief device(s) in gas installations.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
Do not smoke while handling product.
Avoid exposure, obtain special instructions before use.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Avoid suck back of water, acid and alkalis.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Protect containers from physical damage; do not drag, roll, slide or drop.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating valve discontinue use and contact supplier.
Never attempt to repair or modify container valves or safety relief devices.
Damaged valves should be reported immediately to the supplier.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Do not remove or deface labels provided by the supplier for the identification of the content of the container.
Suck back of water into the container must be prevented.
Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon monoxide (630-08-0)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	35 mg/m ³ Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23
WEL TWA (OEL TWA) [2]	30 ppm Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23
WEL STEL (OEL STEL)	232 mg/m ³ Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23
WEL STEL (OEL STEL) [ppm]	200 ppm Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23

Nitric oxide (10102-43-9)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	30 mg/m ³ Limit applicable to underground mining & tunnelling industries ONLY until 21/8/23
WEL TWA (OEL TWA) [2]	25 ppm Limit applicable to underground mining & tunnelling industries ONLY until 21/8/23

Carbon monoxide (630-08-0)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	117 ppm
Acute - systemic effects, inhalation	117 mg/m ³
Long-term - local effects, inhalation	23 ppm
Long-term - systemic effects, inhalation	23 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Product to be handled in a closed system and under strictly controlled conditions.
Provide adequate general and local exhaust ventilation.
Preferably use permanent leak-tight installations (e.g. welded pipes).
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when toxic gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection

: Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

• Skin protection

- Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other : Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Consult respiratory device supplier's product information for the selection of the appropriate device.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Mixture contains one or more component(s) which have the following colour(s):
Colourless Brownish gas.

Odour

- : Odour threshold is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour:
Pungent. Stenchant often added. Sweetish.

Melting point / Freezing point

- : Not applicable for gas mixtures.

Boiling point

- : Not applicable for gas mixtures.
It is technically not possible to determine the boiling point or range of this mixture.
Component with lowest boiling point: Nitrogen -196 °C

Flammability

- : Non flammable.

Lower explosion limit

- : Not available.

Upper explosion limit

- : Not available.

Flash point

- : Not applicable for gas mixtures.

Auto-ignition temperature

- : Non flammable.

Decomposition temperature

- : Not applicable.

pH

- : Not applicable for gas mixtures.

Viscosity, kinematic

- : Not applicable.

Water solubility [20°C]

- : Mixture is partially soluble in water

Partition coefficient n-octanol/water (Log Kow)

- : Not applicable for gas mixtures.

Vapour pressure [20°C]

- : Not applicable.

Vapour pressure [50°C]

- : Not applicable.

Density and/or relative density

- : Not applicable.

Relative vapour density (air=1)

- : Lighter or similar to air.

Particle characteristics

- : Not applicable.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

- Explosive properties : Not applicable.
- Explosion limits : Non flammable.
- Oxidising properties : Not applicable.

9.2.2. Other safety characteristics

Molar mass : Not applicable for gas mixtures.
Evaporation rate : Not applicable for gas mixtures.
Other data : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.
Data for mixture are not available.
This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants. Violently oxidises organic material.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

None.
For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Harmful if inhaled.

Carbon monoxide (630-08-0)	
LC50 Inhalation - Rat [ppm]	3760 ppm/1h (ADR) 1300 ppm/4h (CLP)
Nitric oxide (10102-43-9)	
LC50 Inhalation - Rat [ppm]	57.5 ppm/4h
Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	20000 ppm/4h

Skin corrosion/irritation : Classification criteria are not met.
Serious eye damage/irritation : Classification criteria are not met.
Respiratory or skin sensitisation : No known effects from this product.
Germ cell mutagenicity : No known effects from this product.
Carcinogenicity : No known effects from this product.
Toxic for reproduction : Fertility : No known effects from this product.
Toxic for reproduction : unborn child : May damage the unborn child.
STOT-single exposure : No known effects from this product.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l] : No data available.
EC50 72h - Algae [mg/l] : No data available.
LC50 96 h - Fish [mg/l] : No data available.

Carbon dioxide (124-38-9)

EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Carbon monoxide (630-08-0)

EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Nitric oxide (10102-43-9)

EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Propane (74-98-6)

EC50 48h - Daphnia magna [mg/l]	27.1 mg/l
EC50 72h - Algae [mg/l]	11.9 mg/l
LC50 96 h - Fish [mg/l]	49.9 mg/l

Nitrogen (7727-37-9)

EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : No data available.
Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment :

12.7. Other adverse effects

Other adverse effects : No known effects from this product.
Effect on the ozone layer : No effect on the ozone layer.
Effect on global warming : Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Must not be discharged to atmosphere.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 1956

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : COMPRESSED GAS, N.O.S. (Nitrogen, Nitric oxide)
Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, n.o.s. (Nitrogen, Nitric oxide)
Transport by sea (IMDG) : COMPRESSED GAS, N.O.S. (Nitrogen, Nitric oxide)

14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 1A
Hazard identification number : 20
Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable.
Transport by air (ICAO-TI / IATA-DGR) : Not applicable.
Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.
Transport by air (ICAO-TI / IATA-DGR)
Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : Restricted to professional users (Annex XVII REACH).
Contains no substance on the REACH candidate list.
Other information, restriction and prohibition regulations : Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Seveso Directive : 2012/18/EU (Seveso III) : Not covered.

National regulations

Regulatory reference : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Safety Data Sheet

4 Component mix in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Reference number: SDS 00589

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate.
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
EINECS - European Inventory of Existing Commercial Chemical Substances.
CAS# - Chemical Abstract Service number.
PPE - Personal Protection Equipment.
LC50 - Lethal Concentration to 50 % of a test population.
RMM - Risk Management Measures.
PBT - Persistent, Bioaccumulative and Toxic.
vPvB - Very Persistent and Very Bioaccumulative.
STOT- SE : Specific Target Organ Toxicity - Single Exposure.
CSA - Chemical Safety Assessment.
EN - European Standard.
UN - United Nations.
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.
IATA - International Air Transport Association.
IMDG code - International Maritime Dangerous Goods.
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.
WGK - Water Hazard Class.
STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.
UFI : Unique Formula Identifier.

Training advice

: Users of breathing apparatus must be trained.
Ensure operators understand the toxicity hazard.

Further information

: Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : <http://www.eiga.eu>.
Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Gas 1B	Flammable gases, Category 1B
H220	Extremely flammable gas.
H221	Flammable gas.
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

4 Component mix in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Reference number: SDS 00589

Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 1A	Reproductive toxicity, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document